

## Data sheet Circum-MINI

Item number	Nominal diameter DN	Sleeve length	total Ø roll up size incl. rubber	Stainless steel sleeve V4A			EPDM Rubber seal			Suitable for pipes		Maximum sealing zone for single displacement	weight
				Metal sheet thickness	Roll-up size	Extended dimension max.	Thick-ness rubber surface	Height sealing lips	Rubber thick-ness incl. Sealing lips	min	max.		
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
1-150 Mini	150	400	129	1,0	117	154	2,0	5,0	7,0	140	156	310	2,11
1-200 Mini	200	400	164	1,2	150	204	2,0	5,0	7,0	175	208	310	3,2
1-250 Mini	250	420	194	1,2	190	254	2,0	5,0	7,0	215	260	330	4,4
1-300 Mini	300	420	249	1,2	235	306	2,0	6,0	8,0	260	312	330	5,2
1-400 Mini	400	420	339	1,5	325	407	2,0	8,0	10,0	355	413	330	8,1
1-500 Mini	500	450	444	1,5	420	506	2,0	8,0	10,0	460	516	330	10,6
1-600 Mini	600	450	524	2,0	510	610	2,0	8,0	10,0	560	620	330	13,3
1-700 Mini	700	450	614	2,0	600	714	2,0	8,0	10,0	640	724	330	
1-800 Mini	800	450	714	2,0	700	810	2,0	8,0	10,0	740	830	330	

All sleeves are available: not flared/ one end flared / flared on both sides . Please indicate on the order!

**DN 150 – 500 suitable for serial installation**

**DN 600 - 800 only for single installation**